

ANTlabs

Connectivity **Made Easy**

A N T L A B S C A T A L O G



ANTLABS

- Models
- Capacity
- Features
- Install Assistance

www.peaceysystems.com
sales@peaceysystems.com
1.888.490.3773



ANTLABS M100

PERFECT FOR 100 - 300 USER DEPLOYMENT SITES.

- MOTELS
- HOSTELS
- CLUBS
- RESTAURANTS

SUPPORT FOR UP TO 300 VLANs.

SHIPPING WEIGHT: 6 LBS.



ANTLABS E500

TELCO-GRADE PLATFORM FOR 500 - 1000 USERS.

- HOTELS
- AIRPORTS
- MALLS
- EXHIBITION CENTERS

SUPPORT FOR UP TO 2000 VLANs.

SHIPPING WEIGHT: 60 LBS.



ANTLABS G1500

TELCO-GRADE PLATFORM FOR 1500 - 4000 USERS.

- WISPs
- HOTELS
- AIRPORTS
- MALLS
- EXHIBITION CENTERS

SUPPORT FOR UP TO 4000 VLANs.

SHIPPING WEIGHT: 80 LBS.



InnGate 3 Model	M-Series		
	IG3-100	IG3-200	IG3-300
Default User License ¹	100	200	300
Max User License	300	300	300
Max VLANs ²	300	300	300
Max Throughput ³	300 Mbps		
Max PPS	30,000		
Ethernet	GbE WAN, LAN, HA Port		
COM	1 x RS232 (DB9) Console Port 1 x RS232 (DB9) PMS Port		
Power Consumption	20 W		
Nett Weight	1.5 kg		
Dimensions	272(W) x 156(D) x 44(H) mm		
Certification	CE, FCC, ROHS		



InnGate 3 Model	E-Series					
	IG3-250	IG3-500	IG3-750	IG3-1000	IG3-1500	IG3-2000
Default User License ¹	250	500	750	1,000	1,500	2,000
Max User License	2,000	2,000	2,000	2,000	2,000	2,000
Max VLANs ²	1,000	1,000	1,000	1,000	1,000	1,000
Max Throughput ³	946 Mbps					
Max PPS	130,000					
Ethernet	1 x GbE WAN Port, 1 x GbE LAN Port, 1 x GbE HA Port					
COM	1 x RS232 (DB9) PMS Port, 1 x USB Serial Console Port					
Power Consumption	250 W					
Nett Weight	8.1 kg					
Dimensions	431(W) x 394(D) x 43(H) mm					
Certification	CE, FCC, ROHS					



InnGate 3 Model	G-Series				
	IG3-1500X	IG3-2000X	IG3-2000	IG3-3000	IG3-4000
Default User License ¹	1,500	2,000	2,000	3,000	4,000
Max User License	2,000	2,000	4,000	4,000	4,000
Max VLANs ²	2,000	2,000	1,000	1,000	1,000
Max Throughput ³	946 Mbps				
Max PPS	160,000				
Ethernet	1 x GbE WAN Port, 1 x GbE LAN Port, 1 x GbE HA Port				
COM	1 x RS232 (DB9) PMS Port, 1 x USB Serial Console Port				
Power Consumption	480 W				
Nett Weight	16 kg				
Dimensions	437(W) x 610(D) x 87(H) mm				
Certification	CE, FCC, ROHS				

ANTlabs InnGate 3

Product Data Sheet Feature List

Plug and Play Zero-configuration Networking Reporting Features

- Supports both static and dynamic (DHCP) IP addresses - Real-time reporting on authenticated guest
- Adaptive Domain Name Services (DNS) support - Real-time reporting on detected devices
- Transparent Simple Mail Transfer Protocol (SMTP) support - Guest access logging
- Transparent web proxy support - Device access logging
- Application NAT support (VPN, SIP, RSTP, MMS, H323) - Web-page access logging
- Exportable logs

Multiple Authentication and Billing

Complimentary Access Security Features

- User ID and Password Authentication (Local Accounts) - URL / Content Filtering
- Access Codes Authentication (Local Accounts) - Access Control to Web Administration GUI
- PMS Authentication and Billing - MAC-based blacklist
- Credit Card Authentication and Billing - Anti-Spam features (Worldpay, Authorize.net, Payflow Pro, Payflow Link) - Anti-DoS features
- MAC-level authentication for non-HTTP devices - DoS event alerts
- Configurable Plan-based Firewall

Concurrent / Multiple Business Model Support

- 802.1Q VLAN security
- Unlimited Duration and Volume - Web session rate limit
- Fixed Duration
- Stored Duration

System Administration Features

- Stored Volume – 2 modes (logout, throttled) - Secure HTTPS connection to Administrator page
- Two tier Console CLI support

PMS support - Configurable Tiered Access for Web Administration

- TCP/IP : Fidelio / Opera - Admin Access Audit Logs
- Serial : Fidelio / Opera, FCS, Jurudata, Votech, HIS, Hobic, RoomMaster, Comanche, Brilliant, Prologic, Control, Protel

System Management Features

- SNMPv2 Support

Guest Management Features - Network Time Protocol (NTP) server support

- Auto Logout of inactive guests - File Transfer Protocol (FTP) server
- Forced Logout of guests - Configurable DHCP Server / Relay support
- Departed Device Detection and Logout - Remote Syslog Support
- Bandwidth Rate Limit - User Provisioned Routable Public IP address for clients
- Concurrent login sessions per subscriber account - External HTTP Web Proxy support
- Location specific login concurrency limit - Remote edge device (switches / hubs / access points)

Monitoring

- Multiple IP for Network Address Port Translation (NAPT)

Guest Content Features - Secure Socket Layer (SSL) certificate management

- HTTP / HTTPS / IP Walled-garden
- Email Login Reminder

Reliability Features

- PDA / PDA-phone friendly - High Availability Offering (Active-standby)
- Location / VLAN-based content delivery - Configuration Backup and Restore Function
- Unique login pages for separate locations (Login / Login-Success / Logout)

www.peaceysystems.com

sales@peaceysystems.com

1.888.490.3773

For sales and installation assistance please call 888 490 3773 or email sales@peaceysystems.com

www.peaceysystems.com
sales@peaceysystems.com
1.888.490.3773